RT - 1 (Duplex)						Zoning Compliance Summary Checklist Buildings & Structures for one & two Family Residential Use				
MAPLE RIDGE			Secondary Suites are not permitted in this		**Please he advised that this handout is a Zoning Pylaw summary only					
		British Colum	bia		ne	Building Permit Number :				
PROPERTY INFORMATION						COVENANTS REGISTERED ON TITLE:				
Address :			111011			Comprehensive De	Y / N			
Lot Depth : Min. Basem			ment El :		Geotechnical :		Y / N			
				ment El :		Fish & Wildlife :		Y / N		
Lot Area :	BCP:					DP-025-02 Area :		Y / N		
Lot # :						Water Managemer	nt:	Y / N		
CETRACICO						Flood Plain :		Y / N		
SETBACKS					Stat. Right-of-Way		Minimum	Y / N Proposed	Complies*	
Principal Structure within			n Town	Front		5.5 metres	m	Complico		
	Centre area				Rear		**7.5 metres	m		
					Left Side		1.5 metres	m		
	Principal & Accessory buildings and stru comply with visual clearance at intersec Section 403.8 of the zoning bylaw				Right Side		1.5 metres	m		
					Side setbacks combined		3.5 metres	m		
					Exterior Side Lot Line		4.5 metres  * City of Maple Ridge	m ge use only		
	Princ	ipal Struc	cture outsi	de Town	n Front		7.5 metres	m m		
		e area			Rear		**7.5 metres	m		
Joshia di da					Left Side		1.5 metres	m		
				Right Side		1.5 metres	m			
						cks combined	3.5 metres	m		
					Exterior S	Side Lot Line	4.5 metres	m		
Detached Garage / Carport					Front Lot	Line	* City of Maple Ridge 7.5 metres	ge use only m		
						Line TC area	5.5 metres	m		
other Accessory structure				Rear Lot			1.5 metres	m		
						ide Lot Line	1.5 metres	m		
					Exterior Side Lot L		3.0 metres	m		
Separation between/to princi						al residential use	1.5 metres	m		
Min. setback to projections (bay windows, hutches, nooks, etc) from abutting interior side lot line 0.90m (3' - 0") m										
Maximum Roof projection into the required interior side yard 0.60m (2' - 0")										
Maximum Roof projection <b>into</b> front, rear or exterior side yard setbacks 1.25m (4' - 1")								m		
Dwelling's	Corner	Grade Ele	vations	AVERAGE F	INISHED GRA	ADE (lot grading plans	s) please see revers	е		
(in meters) Left Right			((Add Lowest of existing or proposed grades at all exterior corner							
Front finished gr. a) c)			(4 corners minimum ))/ (# of corners used, 4 min)=				m			
Rear finished gr. b) d)			AVERAGE NATURAL GRADE (No lot grading plan) please see re- ((Add Lowest of existing or proposed grades at all exterior corners							
Front Existing gr. e) g) Rear Existing gr. f) h)			(4 corners minimum ))/ (# of corners used, 4 min)=				m			
BUILDING HEIGHT										
Building Height measured to Mid Point between Main Roof Ridge and Eave of Heighest Storey for roof pitch ≥ 4:12  Building Height measured to Highest point of THE Roof for Flat roofs or where the roof pitch < 4:12										
									Complies	
Principal Building Accessory buildings & Structures					9.5 metres 4.5 metres		m m			
HIGHEST BUILDING FACE					<b>I</b>	-	Maximum	1	Complies	
complies with sloping 7 m Highest Building Face line					(from ovinting gradue)		7.0m	Proposed	Compiles	
complies with sloping 7 m Highest Building Face							7.0m	m m		
40% exemption rule applied?				IS 1 400 III10	Y / N		40%	%		
					1.0 metre in height require P.Eng des		ocida	Proposed	Complies	
RETAINING WALLS: maximum 1.20 m (4' - 0") height						+ , , , , , , , , , , , , , , , , , , ,			Compiles	
					1		- 6	m	/:	
LOT COVERAGE  All buildings & Structures				Maximum %	Proposed %	Maximum are	ea (in metric)		ea (in metric)	
			ures	40% 15%	% lesser of 279m <sup>2</sup> or 15%		$ \begin{array}{c cc}  & m^2 & m^2 \\  & m^2 & m^2 \end{array} $			
Accessory buildings & Structures 1  **Where a high pressure gas main right-of-way is lo					1 70	100001 01 27 9111 01 10%		Stamp area (for City use only)		
rear lot line,	the set	back shall b	d rear setback e not less that of the building	n 5 metres						
Planchecker : Date :										

City of Maple Ridge Revised Feb 2021

## **BUILDING HEIGHT:**


- 1. The Building Height shall be measured as the vertical distance from either:
  - a. the Average Finished Grade, or
  - the Average Natural Grade for subdivisions of less than three (3) Lots and for infill Developments which are not required by the Municipal Engineering Department to provide a Comprehensive Lot Grading Plan,

## LOCALIZED DEPRESSION:

- 1. an existing localized depression in Natural Grade not exceeding 3 metres (9.8ft.) in width, or 20% of the building length that it abuts, whichever is less;
- 2. a localized depression below Finished Grade providing vehicle or pedestrian entrances to a building shall be subject to the following conditions:
  - a. only one vehicle entrance and one pedestrian entrance are shall be considered as Localized Depressions on a single family or two unit residential building.
  - on any side of the building in a single detached or two unit residential building, the Localized Depression width shall not exceed the lesser of 50% of the corresponding building width or:
    - i. 6.0m (20 ft.) width for vehicle access.
    - ii. 2.44m (8 ft.) wide 3.0 m² in area for a pedestrian access, or
    - iii. 7.3m (24 ft.) wide for a combined vehicle and pedestrian access
  - where a localized depression for a pedestrian entrance is completely covered by a deck attached to the storey immediately above it, the localized depression shall be exempt.
  - 4. any combination of vehicle or pedestrian entrances and exist ing depressions remaining after finish grading shall not exceed 50% of the corresponding building width or length along any side of a building.

## HIGHEST BUILDING FACE EXEMPTIONS:

- a. a maximum 40% of the length of the building face can be exempt from this regulation.
   Different portions of the building face can be exempted, provided that the sum of their lengths does not exceed 40% of the total length of the building face;
- b. roof eaves, decks, decorative features, and the pitched roof portion of either gable ends or dormers are exempt:
- c. any portion of the roof Structure above the top plate is exempt from this calculation; and
- d. 100% of the length of the rear Building Face is exempt for Lots where the entire Rear Lot Line abuts land dedicated by subdivision for Park purposes within which a Watercourse exists, as identified on Schedule "C" Natural Features of the Maple Ridge Official Community Plan Bylaw No. 7060-2014 or the Streamside Setback Assessment Map of the Maple Ridge Watercourse Protection Bylaw No. 6410-2006, provided that the rear Building elevation is identified as the highest Building Face.



(a) Localized Depression in natural grade

