Zoning Compliance Summary Checklist RS - 3 (Single Family) Buildings & Structures for one Family Residential Use **Please be advised that this handout is a Zoning Bylaw summary only. Fill for house construction is MAPLE RIDGE See Zoning bylaw for complete information.** limited to 7.5m beyond building face to toe of fill on British Columbia ALR lots **Building Permit Number:** PROPERTY INFORMATION **COVENANTS REGISTERED ON TITLE:** Address :_ Comprehensive Design: Geotechnical: Lot Depth: Min. Basement El:__ Y / N Prop. Basement EI:_____ Lot Width:_____ Fish & Wildlife: Y / N Lot Area : _____ DP30 Area: Y / N Water Management: Lot # Y / N Flood Plain: Y / N SETBACKS Stat. Right-of-Way: Y / N Minimum Proposed Complies* Principal Structure Front 7.5 metres **7.5 metres Rear Left Side 1.5 metres m Right Side 1.5 metres Principal & Accessory buildings and structures must 3.5 metres comply with visual clearance at intersections per Side setbacks combined ection 403.8 of the zoning bylaw Exterior Side Lot Line 4.5 metres m City of Maple Ridge use only Front Lot Line 7.5 metres Detached Garage / Carport & Rear Lot Line 1.5 metres other Accessory structures Interior Side Lot Line 1.5 metres m Exterior Side Lot Line 3.0 metres Separation between/to principal residential use 1.5 metres m Min. setback to projections (bay windows, hutches, nooks, etc) from abutting interior side lot line 0.90m (3' - 0") Maximum Roof projection into the required interior side yard **0.60m (2' - 0")** Maximum Roof projection into front, rear or exterior side yard setbacks 1.25m (4' - 1") m AVERAGE FINISHED GRADE (lot grading plans) please see reverse **Dwelling's Corner Grade Elevations** Left Right ((Add Lowest of existing or proposed grades at all exterior corners) (in meters) Front finished gr. (4 corners minimum))/ (# of corners used, 4 min) Rear finished gr. AVERAGE NATURAL GRADE (No lot grading plan) please see reverse Front Existing gr. ((Add Lowest of existing or proposed grades at all exterior corners) Rear Existing gr. (4 corners minimum))/ (# of corners used, 4 min) BUILDING HEIGHT Building Height measured to Mid Point between Main Roof Ridge and Eave of Heighest Storey for roof pitch ≥ 4:12 Building Height measured to Highest point of THE Roof for Flat roofs or where the roof pitch < 4:12 **BUILDING HEIGHT of:** Proposed Complies Roof pitch Maximum height permitted Principal Building 9.5 metres Detached Parking/Accessory structure 6.0 metres HIGHEST BUILDING FACE Maximum Proposed Complies complies with sloping 7 m Highest Building Face line (from existing grades) 7.0m m complies with sloping 7 m Highest Building Face line (from finished grades) 7.0m m 40% 40% exemption rule applied? **RETAINING WALLS** walls over 1.0 metre in height require P.Eng design Proposed Complies RETAINING WALLS: maximum 1.20 m (4' - 0") height LOT COVERAGE Maximum % Proposed % Maximum area (in metric) Proposed area (in metric) All buildings & Structures total 40% m^2 Accessory buildings & Structures 15% lesser of 279m2 or 15% m² Stamp area (for City use only) **Where a high pressure gas main right-of-way is located within any portion of the required rear setback area from a rear lot line, the setback shall be not less than 5 metres from the right of way to the rear of the buildings closest projection.

City of Maple Ridge Revised Feb 2021

Date : ___

Planchecker: ___

BUILDING HEIGHT:


- 1. The Building Height shall be measured as the vertical distance from either:
 - a. the Average Finished Grade, or
 - the Average Natural Grade for subdivisions of less than three (3) Lots and for infill Developments which are not required by the Municipal Engineering Department to provide a Comprehensive Lot Grading Plan,

LOCALIZED DEPRESSION:

- 1. an existing localized depression in Natural Grade not exceeding 3 metres (9.8ft.) in width, or 20% of the building length that it abuts, whichever is less;
- a localized depression below Finished Grade providing vehicle or pedestrian entrances to a building shall be subject to the following conditions:
 - a. only one vehicle entrance and one pedestrian entrance are shall be considered as Localized Depressions on a single family or two unit residential building.
 - on any side of the building in a single detached or two unit residential building, the Localized Depression width shall not exceed the lesser of 50% of the corresponding building width or:
 - i. 6.0m (20 ft.) width for vehicle access.
 - ii. 2.44m (8 ft.) wide 3.0 m² in area for a pedestrian access, or
 - iii. 7.3m (24 ft.) wide for a combined vehicle and pedestrian access
 - where a localized depression for a pedestrian entrance is completely covered by a deck attached to the storey immediately above it, the localized depression shall be exempt.
 - 4. any combination of vehicle or pedestrian entrances and exist ing depressions remaining after finish grading shall not exceed 50% of the corresponding building width or length along any side of a building.

HIGHEST BUILDING FACE EXEMPTIONS:

- a. a maximum 40% of the length of the building face can be exempt from this regulation.
 Different portions of the building face can be exempted, provided that the sum of their lengths does not exceed 40% of the total length of the building face;
- b. roof eaves, decks, decorative features, and the pitched roof portion of either gable ends or dormers are exempt:
- c. any portion of the roof Structure above the top plate is exempt from this calculation; and
- d. 100% of the length of the rear Building Face is exempt for Lots where the entire Rear Lot Line abuts land dedicated by subdivision for Park purposes within which a Watercourse exists, as identified on Schedule "C" Natural Features of the Maple Ridge Official Community Plan Bylaw No. 7060-2014 or the Streamside Setback Assessment Map of the Maple Ridge Watercourse Protection Bylaw No. 6410-2006, provided that the rear Building elevation is identified as the highest Building Face.



(a) Localized Depression in natural grade

